

All-in-one POS Terminal Solution



DesirePOS



Variety of color choice
Red, Dark Gray, White

LCD LED BACKLIGHT

- 15" flat touch screen technology
- Intel Atom DualCore / IvyBridge B960/i3/i5 processor
- 100% Fan-less design
- Elegant with small foot print design
- Combinations of multi-colors White/Dark Grey/Red



Magnetic card reader.



Dual LCD monitors.




Flat touch screen.



Customer display.



Fashionable back-side design.



Splash proof.

Peripheral Options



System	
CPU Support	Intel® Atom Dual Core D525 1.8Ghz CPU Intel® Pentium® Processor B960 Intel® IVY Bridge Intel® Core i5 / i3 / Dual Cores CPU Intel® Celeron® Processor Bay-Trail J1900 (2M Cache , up to 2.42GHz)
Memory	Support up to 4GB DDR3(D525) Support up to 8GB DDR3(Baytrail and HM76)
Core Logic	Intel NM10 / HM76 / BayTrail
Network	10/100/1000 Base-T Fast Ethernet
Power Supply	12V Power Adaptor
System weight	9 kgs
Dimension (WxHxD)	380x 370 x 190mm
O/S Compliant	Windows XP/XPE, WEPOS, POSReady 2009, Win 7, Win8 (Ivy Bridge and Baytrail platform only)
Storage	
HDD	1 x 2.5" SATA HDD
SSD	SSD interface Max.512GB
I/O Ports	
USB	7 ports, 3 internal (one reserved for touch screen) and 4 external.
Serial Ports	6 x COM (w/ +5V, +12V selectable), 2 internal and 4 external.
PS/2	1 x PS/2 keyboard port
LAN	1 x 10/100/1000 Mbps (RJ45)
VGA	1 x DB-15 VGA Interface
Parallel	1xDB25
Audio	AC'97 Codec Audio
Cash Drawer	1xRJ11
DC-IN	12V DC-IN
Power Switch	1 x Power Switch
Display	
LCD	15" TFT LCD Panel
Max. Resolution	1024 x 768
Brightness	250 nits
Touch Screen	5 Wire resistive touch panel
Peripheral Options	
Printer	TP-260
Customer Display	VFD Type: 20 columns x 2 lines, each column 5x7 dots LCD Type: 8", 10" or 15" LCD
MSR	JIS-I or II, ISO Track 1/2/3 USB (default)
i-button	Read only, USB interface
Color	Dark Grey
Fingerprint	Fingerprint module (USB HID interface)
RFID	ISO 14443A, UltraLight, Mifare@PRO, DESfire